



# PNEUMATIC TRAILERS

## ADVANTAGES

### Standard Dry Bulk Pneumatics and Vacuum Styles

- Low Cube: 1000, 1050, 1250, 1350, 1480
- High Cube: 1600, 1615, 1650, 1850, 2000
- Vacuum Pneumatic Tanks also available: 1600V, 1650V, 1850V, 2000V
- Internal or External Aeration piping available
- Canadian Models available: B-Train, Tridem RTAC, Quad Axle, Five Axle and Six Axle



Low Cube



Vacuum Pneumatic Tank



High Cube



### AeroMAC 1615

- Monocoque frameless design, 100% clean bore smooth interior with external rings, front and rear void section. Transition Walkway with handrails, 102" wide low center of gravity, optional washout nipple and food grade Aerators and hoses. Easily removable Cam-On couplings, wiring and airline accessibility.

E X P E R I E N C E   E X C E L L E N C E

# ALL STANDARD WITH:



- **Standard 2" BTI individual aeration control butterfly valves** for maximum air volume control and maximum trailer versatility.



- **Gauge box mounted on a 45 degree angle for better visibility** with light inside box for night time operation.



- **Standard BTI product valves with 14" handle extension** for easy operation without having to crawl under the trailer.



- **Nuisance dust from the blow-down process exhausts below the frame** and outboard away from the driver.



- **Hose tubes reinforced at both ends** to prevent damage from product hose ends. Formed hose tube support is a bolted easy to replace design.



- **Light weight modular component designs** such as the bumper and light boxes are easily repaired or replaced.




- **Standard galvanized Hendrickson AAT23K suspension** and galvanized bracing with raised center parallel spindle axles and chip-resistant long lasting soft coat finish.



- **Standard Jost 10-year limited warranty, no-lube, 150,000 lbs. rated landing gear** with corrosion resistant aluminum pipe bracing.



- **Straight under axle discharge** ensures fast unloading times and reduces pipe wear.



- **Formed one piece fender brackets** bolted to high strength aluminum angles are easily maintained or replaced when damaged.



- **Standard sealed 10 year warranted modular wiring harness** used throughout trailer resists corrosion from road salts.



- **Standard heavy duty galvanized 5th wheel plate** resists corrosion and extends service life.



- **The MAC Stairs raise the bar in driver comfort.** Continuous auxiliary handrails afford three points of contact up and down the ladder. Convenient upper and lower grab handles for comfortable transition on and off the trailer. Integrated ergonomically placed stair steps allow you to climb the ladder in an upright stance without the feeling of falling backwards.



- **Mandrel bent piping used throughout the trailer allows for unobstructed air and or product flow,** thereby reducing the heat and friction created by turbulent air low in the lines, for faster unloading and less product degradation.

Scan Code to



Visit our Website

Follow Us!



**1-800-795-8454**  
**www.MACTrailer.com**

